

Python For Data Science

Keras Cheat Sheet

Learn Keras online at www.DataCamp.com

Keras

Keras is a powerful and easy-to-use deep learning library for Theano and TensorFlow that provides a high-level neural networks API to develop and evaluate deep learning models.

A Basic Example

```
>>> import numpy as np
>>> from keras.models import Sequential
>>> from keras.layers import Dense
>>> data = np.random.random((1000,100))
>>> labels = np.random.randint(2,size=(1000,1))
>>> model = Sequential()
>>> model.add(Dense(32,
    activation='relu',
    input_dim=100))
>>> model.add(Dense(1, activation='sigmoid'))
>>> model.compile(optimizer='rmsprop',
    loss='binary_crossentropy',
    metrics=['accuracy'])
>>> model.fit(data,labels,epochs=10,batch_size=32)
>>> predictions = model.predict(data)
```

Data

Your data needs to be stored as NumPy arrays or as a list of NumPy arrays. Ideally, you split the data in training and test sets, for which you can also resort to the `train_test_split` module of `sklearn.cross_validation`.

Keras Data Sets

```
>>> from keras.datasets import boston_housing, mnist, cifar10, imdb
>>> (x_train,y_train),(x_test,y_test) = mnist.load_data()
>>> (x_train2,y_train2),(x_test2,y_test2) = boston_housing.load_data()
>>> (x_train3,y_train3),(x_test3,y_test3) = cifar10.load_data()
>>> (x_train4,y_train4),(x_test4,y_test4) = imdb.load_data(num_words=20000)
>>> num_classes = 10
```

Other

```
>>> from urllib.request import urlopen
>>> data =
np.loadtxt(urlopen("http://archive.ics.uci.edu/ml/machine-learning-databases/pima-indians-diabetes/pima-indians-diabetes.data"),delimiter=",")
>>> X = data[:,0:8]
>>> y = data[:,8]
```

Preprocessing

Sequence Padding

```
>>> from keras.preprocessing import sequence
>>> x_train4 = sequence.pad_sequences(x_train4,maxlen=80)
>>> x_test4 = sequence.pad_sequences(x_test4,maxlen=80)
```

One-Hot Encoding

```
>>> from keras.utils import to_categorical
>>> Y_train = to_categorical(y_train, num_classes)
>>> Y_test = to_categorical(y_test, num_classes)
>>> Y_train3 = to_categorical(y_train3, num_classes)
>>> Y_test3 = to_categorical(y_test3, num_classes)
```

> Model Architecture

Sequential Model

```
>>> from keras.models import Sequential
>>> model = Sequential()
>>> model2 = Sequential()
>>> model3 = Sequential()
```

Multilayer Perceptron (MLP)

Binary Classification

```
>>> from keras.layers import Dense
>>> model.add(Dense(12,
    input_dim=8,
    kernel_initializer='uniform',
    activation='relu'))
>>> model.add(Dense(8,kernel_initializer='uniform',activation='relu'))
>>> model.add(Dense(1,kernel_initializer='uniform',activation='sigmoid'))
```

Multi-Class Classification

```
>>> from keras.layers import Dropout
>>> model.add(Dense(512,activation='relu',input_shape=(784,)))
>>> model.add(Dropout(0.2))
>>> model.add(Dense(512,activation='relu'))
>>> model.add(Dropout(0.2))
>>> model.add(Dense(10,activation='softmax'))
```

Regression

```
>>> model.add(Dense(64,activation='relu',input_dim=train_data.shape[1]))
>>> model.add(Dense(1))
```

Convolutional Neural Network (CNN)

```
>>> from keras.layers import Activation,Conv2D,MaxPooling2D,Flatten
>>> model2.add(Conv2D(32,(3,3),padding='same',input_shape=x_train.shape[1:]))
>>> model2.add(Activation('relu'))
>>> model2.add(Conv2D(32,(3,3)))
>>> model2.add(Activation('relu'))
>>> model2.add(MaxPooling2D(pool_size=(2,2)))
>>> model2.add(Dropout(0.25))
>>> model2.add(Conv2D(64,(3,3), padding='same'))
>>> model2.add(Activation('relu'))
>>> model2.add(Conv2D(64,(3,3)))
>>> model2.add(Activation('relu'))
>>> model2.add(MaxPooling2D(pool_size=(2,2)))
>>> model2.add(Dropout(0.25))
>>> model2.add(Flatten())
>>> model2.add(Dense(512))
>>> model2.add(Activation('relu'))
>>> model2.add(Dropout(0.5))
>>> model2.add(Dense(num_classes))
>>> model2.add(Activation('softmax'))
```

Recurrent Neural Network (RNN)

```
>>> from keras.layers import Embedding,LSTM
>>> model3.add(Embedding(20000,128))
>>> model3.add(LSTM(128,dropout=0.2,recurrent_dropout=0.2))
>>> model3.add(Dense(1,activation='sigmoid'))
```

> Prediction

```
>>> model3.predict(x_test4, batch_size=32)
>>> model3.predict_classes(x_test4,batch_size=32)
```

Also see NumPy & Scikit-Learn

Train and Test Sets

```
>>> from sklearn.model_selection import train_test_split
>>> X_train5,X_test5,y_train5,y_test5 = train_test_split(x, y,
    test_size=0.33,
    random_state=42)
```

Standardization/Normalization

```
>>> from sklearn.preprocessing import StandardScaler
>>> scaler = StandardScaler().fit(x_train2)
>>> standardized_X = scaler.transform(x_train2)
>>> standardized_X_test = scaler.transform(x_test2)
```

> Inspect Model

```
>>> model.output_shape #Model output shape
>>> model.summary() #Model summary representation
>>> model.get_config() #Model configuration
>>> model.get_weights() #List all weight tensors in the model
```

> Compile Model

MLP: Binary Classification

```
>>> model.compile(optimizer='adam',
    loss='binary_crossentropy',
    metrics=['accuracy'])
```

MLP: Multi-Class Classification

```
>>> model.compile(optimizer='rmsprop',
    loss='categorical_crossentropy',
    metrics=['accuracy'])
```

MLP: Regression

```
>>> model.compile(optimizer='rmsprop',
    loss='mse',
    metrics=['mae'])
```

Recurrent Neural Network

```
>>> model3.compile(loss='binary_crossentropy',
    optimizer='adam',
    metrics=['accuracy'])
```

> Model Training

```
>>> model3.fit(x_train4,
    y_train4,
    batch_size=32,
    epochs=15,
    verbose=1,
    validation_data=(x_test4,y_test4))
```

> Evaluate Your Model's Performance

```
>>> score = model3.evaluate(x_test,
    y_test,
    batch_size=32)
```

> Save/ Reload Models

```
>>> from keras.models import load_model
>>> model3.save('model_file.h5')
>>> my_model = load_model('my_model.h5')
```

> Model Fine-tuning

Optimization Parameters


```
>>> from keras.optimizers import RMSprop
>>> opt = RMSprop(lr=0.0001, decay=1e-6)
>>> model2.compile(loss='categorical_crossentropy',
    optimizer=opt,
    metrics=['accuracy'])
```

Early Stopping

```
>>> from keras.callbacks import EarlyStopping
>>> early_stopping_monitor = EarlyStopping(patience=2)
>>> model3.fit(x_train4,
    y_train4,
    batch_size=32,
    epochs=15,
    validation_data=(x_test4,y_test4),
    callbacks=[early_stopping_monitor])
```



<https://data-hub.ir/>



t.me/data_hub_ir



youtube.com/c/datahub1



instagram.com/data_hub_ir



linkedin.com/company/data-hub-ir



github.com/datahub-ir



LIKE US



COMMENT



SHARE